		GT05-01 直通终端接头								
		配管尺寸		产品编号	E	A	B	C	F	F1
		T	P							
Φ6	M10×1	GT05-01-01	4	33.5	9	18.5	14	12		
Φ6	G1/8"	GT05-01-02	4	33.5	9	18.5	14	12		
Φ6	M16×1.5	GT05-01-03	4	37.5	12	18.5	22	12		
Φ6	G3/8"	GT05-01-04	4	37.5	12	18.5	22	12		
Φ6	M20×1.5	GT05-01-05	4	42.5	16	18.5	24	12		
Φ6	G1/2"	GT05-01-06	4	42.5	16	18.5	24	12		
Φ8	M10×1	GT05-01-07	4	34.5	9	18.5	14	14		
Φ8	G1/8"	GT05-01-08	6	34.5	9	18.5	14	12		
Φ8	M16×1.5	GT05-01-09	6	38.5	12	18.5	22	12		
Φ8	G3/8"	GT05-01-10	6	38.5	12	18.5	22	12		
Φ8	M20×1.5	GT05-01-11	6	43.5	16	18.5	24	12		
Φ8	G1/2"	GT05-01-12	6	43.5	16	18.5	24	12		
Φ10	M16×1.5	GT05-01-13	8	39.6	12	19.6	22	19		
Φ10	G3/8"	GT05-01-14	8	39.6	12	19.6	22	19		
Φ10	M20×1.5	GT05-01-15	8	44.6	16	19.6	24	19		
Φ10	G1/2"	GT05-01-16	8	44.6	16	19.6	24	19		
Φ12	M16×1.5	GT05-01-17	10	40.6	12	19.6	22	22		
Φ12	G3/8"	GT05-01-18	10	40.6	12	19.6	22	22		
Φ12	M20×1.5	GT05-01-19	10	45.6	16	19.6	24	22		
Φ12	G1/2"	GT05-01-20	10	45.6	16	19.6	24	22		

终端螺纹引用标准:
 ① JIS B0203 (1981) PT 螺纹
 ② JIS B0203 (1982) R 螺纹
 ③ GB7306-87 R 螺纹
 ④ B. S. 84:1956 BSP 螺纹
 ⑤ ANSI B2.1 NPT 螺纹
 ⑥ GB/T12716-91 Z 螺纹
 ⑦ ZG 螺纹
 ⑧ 还可根据用户需要提供其它螺纹标准和配管规格。


公称压力: 1.6Mpa
 配管尺寸: Φ6-Φ12MM
 使用材料: H62、1Cr18Ni9Ti
 参照标准:(原 K12-36、12-43)

		GT05-02 直通中间接头							
		配管尺寸		产品编号	E	A	C	F	F1
		T							
Φ6		GT05-02-01	4	44	18.5	12	12		
Φ8		GT05-02-02	6	44	18.5	14	12		
Φ10		GT05-02-03	8	48	18.5	17	12		
Φ12		GT05-02-04	10	50	18.5	19	12		


参照标准:(原 K12-38)

		GT05-03 直通中间异径接头							
		配管尺寸		产品编号	E	A	C	C1	F
		T	T1						
Φ8	Φ6	GT05-03-01	4	44	18.5	18.5	14		
Φ10	Φ6	GT05-03-02	4	46	18.5	18.5	17		
Φ10	Φ8	GT05-03-03	6	46	18.5	18.5	17		
Φ12	Φ6	GT05-03-04	4	46	19.6	18.5	19		
Φ12	Φ8	GT05-03-05	6	48	19.6	18.5	19		
Φ12	Φ10	GT05-03-06	8	48	19.6	19.6	19		

参照标准:(原 K12-38)

		GT05-04 弯通终端接头								
		配管尺寸		产品编号	E	HX	B	C	HY	F1
		T	P							
Φ6	M10×1	GT05-04-01	4	28	9	18.5	22	12		
Φ6	G1/8"	GT05-04-02	4	28	9	18.5	22	12		
Φ6	M16×1.5	GT05-04-03	4	32	12	18.5	25	12		
Φ6	G3/8"	GT05-04-04	4	32	12	18.5	25	12		
Φ8	M16×1.5	GT05-04-05	6	28	12	18.5	22	12		
Φ8	G3/8"	GT05-04-06	6	28	12	18.5	22	12		
Φ8	M20×1.5	GT05-04-07	6	32	16	18.5	25	12		
Φ8	G1/2"	GT05-04-08	6	32	16	18.5	25	12		
Φ10	M16×1.5	GT05-04-09	8	36	12	19.6	29	19		
Φ10	M20×1.5	GT05-04-10	8	38	16	19.6	32	19		
Φ10	G1/2"	GT05-04-11	8	38	16	19.6	32	19		
Φ12	M16×1.5	GT05-04-12	10	39	12	19.6	33	22		
Φ12	M20×1.5	GT05-04-13	10	42	16	19.6	30	22		
Φ12	G1/2"	GT05-04-14	10	42	16	19.6	30	22		


注: 任何螺纹规格、螺纹标准都可与任何配管尺寸配对
 参照标准:(原 K12-37)



GT05-05 弯通中间接头

配管尺寸		产品编号	E	C	F	F1	HY
T							
Φ6		GT05-05-01	4	18.5	12	12	28
Φ8		GT05-05-02	6	18.5	14	12	30
Φ10		GT05-05-03	8	18.5	17	12	32
Φ12		GT05-05-04	10	18.5	19	12	36


参照标准:(原 K12-39)



GT05-06 直通终端接头

配管尺寸		产品编号	E	A	B	C	HY	F1
T	P							
Φ6	M10×1	GT05-06-01	4	56	9	18.5	22	12
Φ6	G1/8"	GT05-06-02	4	56	9	18.5	22	12
Φ6	M16×1.5	GT05-06-03	4	64	12	18.5	25	12
Φ6	G3/8"	GT05-06-04	4	64	12	18.5	25	12
Φ8	M16×1.5	GT05-06-05	6	56	12	18.5	22	12
Φ8	G3/8"	GT05-06-06	6	56	12	18.5	22	12
Φ8	M20×1.5	GT05-06-07	6	64	16	18.5	25	12
Φ8	G1/2"	GT05-06-08	6	64	16	18.5	25	12
Φ10	M16×1.5	GT05-06-09	8	72	12	19.6	29	19
Φ10	M20×1.5	GT05-06-10	8	76	16	19.6	32	19
Φ10	G1/2"	GT05-06-11	8	76	16	19.6	32	19
Φ12	M16×1.5	GT05-06-12	10	78	12	19.6	33	22
Φ12	M20×1.5	GT05-06-13	10	84	16	19.6	30	22
Φ12	G1/2"	GT05-06-14	10	84	16	19.6	30	22

注：任何螺纹规格、螺纹标准都可与任何配管尺寸配对



GT05-07 三通中间接头

配管尺寸		产品编号	E	C	F	F1	A	HY
T								
Φ6		GT05-07-01	4	18.5	12	12	56	28
Φ8		GT05-07-02	6	18.5	14	12	60	30
Φ10		GT05-07-03	8	18.5	17	12	64	32
Φ12		GT05-07-04	10	18.5	19	12	72	36

参照标准:(原 K12-40)



GT05-08 四通中间接头

配管尺寸		产品编号	E	C	F	F1	A	HY
T								
Φ6		GT05-08-01	4	18.5	12	12	56	28
Φ8		GT05-08-02	6	18.5	14	12	60	30
Φ10		GT05-08-03	8	18.5	17	12	64	32
Φ12		GT05-08-04	10	18.5	19	12	72	36